



---

## SISPM1040-3248-L Release Notes

**Date: Oct.9, 2019**

**Version: 8.40.1384**

---

### Overview

This release notes covers firmware version v8.40.1384 and MIB file for SISPM1040-3248-L.

### Release Changes and Enhancements

#### [Changes]

---

- \* Modify display method at SNMP OID.
  - SNMP System Temperature:
    - \*Separate out the Celsius and Fahrenheit for different OIDs.
    - \*Only return a numerical value.(Do not change current OID attributes)
- \* Modify OID description.
  - SFP/SFP+ variables:
    - \*Only return numerical value and not include the alpha description. (Do not change current OID attributes)
    - \*Modify OID description.
- \* Add "SNMP Server location" command.
- \* Add Traffic monitor back to DMS.
- \* Add Max Reboot Times, for PoE Auto Checking

#### [Fixed]

---

- \* ROMN: History status lost some data.
- \* ROMN: History Buckets set to 60, but the History Sample Index displays 50 data.
- \* ROMN: Statistics field record interface tx value.
- \* SNMP: After send "no snmp-server community public" & "no snmp-server community privatec" command, the Read Community/Write Community field becomes garbled on Home -> SNMP -> Configuration page.
- \* Non-Multicast MAC address can be set to two port number.
- \* IP: Unable to add an IP Routes.
- \* The admin account privilege level can be modified in the Web UI.
- \* After IGMP snooping global mode is enabled, and send "save start config" and "reload warm", the vlan1 IGMP snooping mode will be disabled.
- \* SNMP: n SNMPv3 Community Configuration, Source mask cannot be set via Web/CLI UI, and Web UI behavior is different from CLI.

- \* SNMP: After sending "no snmp-server community public" & "no snmp-server community private" command, the Read Community/Write Community field becomes garbled on Home -> SNMP -> Configuration page.
- \* Unable to modify sFlow's Agent Configuration & Receiver Configuration via SNMPc.
- \* CLI SFP information is different from Web UI.
- \* LLDP: In Web UI, the LLDP-MED Neighbor Information -> Location information displays the "%XX" message.
- \* execute the "Download config", the disk icon will flash.
- \* LLDP: In Web UI, LLDP-MED Neighbor Information lost Inventory information.
- \* Web: The switch can't be restarted when "non stop poe reboot" is executed via web.
- \* CLI config-if mode entering "ptp" will crash.
- \* CLI has "event group Link-Status", but Web UI don't.
- \* System LED will not light up after boot.
- \* DHCP server is automatically enabled after switch reboot.
- \* Unable to send LLDP trap via TCP mode.
- \* Unable to close PoE mode via Web UI.
- \* PoE delay time can be set more than 0~300 sec.
- \* ACL: ACE IPv6 Parameters "Hop Limit" setting is different from Help.
- \* ACL: CLI's explanation of arp-tmac is different from Web UI.
- \* QoS: Web's Shaper rates available setting is different from CLI.
- \* QoS: In CLI, QCE's action parameters display "ingress-map" parameter.
- \* Web UI-LLDP Neighbor Information cannot display "|".
- \* System information does not show Temperature Degree.
- \* 802.1x: forwarding 1024 different source address packets, Switch will crashes and reboot.
- \* Port: Port Description can set the inconsistency of characters on Web/CLI/SNMP.
- \* Multicast traffic leaks from one Private VLAN to another Private VLAN.
- \* DMS: Upload Floor image, if filename contains a space, the file cannot be deleted.
- \* After entering specific characters on SNMPv3 Community, Add New Entry will failed on Web UI.
- \* WebUI-->IP Address-->Advanced Settings apply to delete ip interface, will shows error: "Cannot delete all interfaces."
- \* SNMP: 10G port speed cannot set to 10G Full via SNMP.
- \* Syslog: Import-Export cannot receive syslog.
- \* https is disabled after reboot.
- \* ACL: Port Policy ID can set the inconsistency of range on Web/CLI/SNMP.
- \* Bug 20196 - CLI log entries are truncated after 96 characters
- \* When switch has only two VLAN Interfaces, it cannot be deleted.
- \* Unable to see IP address assigned by DHCP Server in Web UI.
- \* Unable to read the correct SFP information.
- \* IGMP: After Join/Leave, when the specific query does not reach the RV number, igmp group will be cleaned up.
- \* ICMP Ping ptt.cc will continue to display % Ready for new ping



Transition Networks  
10900 Red Circle Drive  
Minnetonka, MN 55343  
[www.transition.com](http://www.transition.com)

---

- \* The port-security command is executed on all ports in CLI, the CLI will hang, and Web & Ping & Telnet still work.
- \* Port-Security: limit set to "1", only one mac connection will cause the switch shutdown.
- \* Web: Unable to create a VLAN without an IP address.
- \* SNMP: when setting Write community name and read community name are the same, unable to set behavior.
- \* Firmware upgrade will cause switch crashes if switch can't download FW image via TFTP.

### **Known Limitations and Restrictions**

N/A